
PRESSENTIN PARK SIDE CHANNEL RESTORATION


SKAGIT COUNTY, WA



/ICINI	TΥ	MAP
CALE: NTS		

		Sheet List Table
SHEET NO.	DWG NO.	SHEET DESCRIPTION
1	G-1	VICINITY MAP AND SHEET INDEX
2	G-2	LEGEND AND GENERAL NOTES
3	C-1	EXISTING CONDITIONS
4	C-2	SITE PLAN AND PROPOSED WORK
5	C-3	LOWER GRADING AND SITE PLAN
6	C-4	UPPER GRADING AND SITE PLAN
7	C-5	GRADING DETAILS
8	C-6	INLET PLAN AND DETAILS
9	C-7	OUTLET AND FLOODFENCE PLAN AND DETAILS
10	C-8	ELS DETAILS
11	ESC-1	TESC DETAILS

NOTE AND DETAIL/SECTION REFERENCING



"-" INDICATES THAT THE DETAIL/SECTION IS SHOWN ON THE SAME SHEET

"TYP" INDICATES THAT THE DETAIL/SECTION IS UNIFORMLY TYPICAL THROUGHOUT PROJECT EXCEPT WHERE OTHERWISE NOTED

"VAR" SPECIFIES THAT DETAIL/SECTION WAS TAKEN FROM SEVERAL DRAWINGS

CONCEPT - NOT FOR CONSTRUCTION

					HERRERA	
No.	REVISION	BY	APP'D	DATE	TIERRERA	

	DESIGNED:	DRAWN:	
SWASD/	G. KAYS	E. MARSHALL	
NOE WASHING	DESIGNED:	DRAWN:	
E KX E	M. BEGGS	-	
	DESIGNED:	CHECKED:	
E Q GISTERED SE	-	-	
OCIONAL ENGL	SCALE:	APPROVED:	
2001	AS NOTED	M. EWBANK	

PRESSENTIN PARK SIDE CHANNEL RESTORATION

VICINITY MAP AND SHEET INDEX

FEB 2015 14-05789-000 G-1

GENERAL NOTES:

- MATERIAL STAGING AREAS TO BE LOCATED AS SHOWN ON THE SITE PLAN. MATERIAL SHALL NOT BE STORED OUTSIDE OF IDENTIFIED STAGING AREAS, UNLESS APPROVED BY DISTRICT AND LAND OWNER.
- CONTRACTOR SHALL LIMIT MACHINERY MOVEMENT TO PROJECT LIMITS DEFINED ON SITE PLAN OR IDENTIFIED AS ACCEPTABLE TO DISTRICT.
- CLEARING LIMITS FOR TEMPORARY ACCESS ROAD AND PROPOSED STRUCTURES SHALL BE LIMITED TO THE AREA REQUIRED FOR SAFE EQUIPMENT OPERATION. CLEARING LIMITS SHALL BE STAKED BY CONTRACTOR AND APPROVED BY DISTRICT AT LEAST 3 DAYS PRIOR TO CLEARING ACTIVITIES. CLEARING LIMITS SHALL BE STAKED TO MINIMIZE THE AREA OF DISTURBANCE.
- 4. APPROVED CONSTRUCTION SEQUENCE PLAN SHALL NOT BE ALTERED UNLESS
- FIELD VERIFY WITH DISTRICT ALL ENGINEERED LOGJAM LOCATIONS, LENGTHS, WIDTHS, AND ELEVATIONS PRIOR TO EXCAVATION, ASSEMBLY, AND INSTALLATION OF EACH STRUCTURE.
- EQUIPMENT USED FOR THIS PROJECT SHALL BE FREE OF EXTERNAL PETROLEUM-BASED PRODUCTS WHILE WORKING NEAR OR ANY SURFACE WATER OR WETLANDS. ACCUMULATION OF SOILS OR DEBRIS SHALL BE REMOVED FROM THE DRIVE MECHANISMS (WHEELS, TRACKS, TIRES, ETC.) AND UNDERCARRIAGE OF EQUIPMENT PRIOR TO ITS WORKING BELOW THE BANKFULL WATER ELEVATION.
- 7. EQUIPMENT SHALL BE CHECKED DAILY FOR LEAKS, AND ANY NECESSARY REPAIRS SHALL BE COMPLETED PRIOR TO COMMENCING WORK ACTIVITIES.
- THE CONTRACTOR IS RESPONSIBLE TO ENSURE THAT NO PETROLEUM PRODUCTS, HYDRAULIC FLUID, SEDIMENTS, SEDIMENT-LADEN WATER CHEMICALS, OR ANY OTHER TOXIC OR DELETERIOUS MATERIALS ARE ALLOWED TO ENTER OR LEACH INTO THE RIVER, GROUNDWATER, OR WETLANDS.
- 9. IF AT ANY TIME, AS A RESULT OF PROJECT ACTIVITIES, FISH ARE OBSERVED IN DISTRESS, A FISH KILL OCCURS, OR WATER QUALITY PROBLEMS DEVELOP (INCLUDING EQUIPMENT LEAKS OR SPILLS), OPERATIONS SHALL CEASE AND THE DISTRICT SHALL BE NOTIFIED IMMEDIATELY. WASHINGTON DEPARTMENT OF FISH AND WILDLIFE AND WASHINGTON DEPARTMENT OF ECOLOGY SHALL BE CONTACTED IMMEDIATELY BY THE DISTRICT OR BY HIS/HER DESIGNEE. WORK SHALL NOT RESUME UNTIL FURTHER APPROVAL BY DISTRICT REPRESENTATIVE.
- 10. EROSION CONTROL METHODS SHALL BE USED TO PREVENT SILT-LADEN WATER FROM ENTERING THE RIVER. INITIAL EROSION CONTROL MEASURES ARE SHOWN ON DRAWINGS C-3, AND C-4. CONTRACTOR IS SOLELY RESPONSIBLE FOR SUITABLE BMP'S TO CONTROL SILTATION FROM WORK AREA
- 11. ALTERATION OR DISTURBANCE OF THE BANK AND BANK VEGETATION SHALL BE MINIMIZED TO THAT NECESSARY TO CONSTRUCT THE PROJECT. CONTRACTOR SHALL KEEP DISTURBED AREAS WITHIN LIMITS SHOWN ON PLANS.
- 12. IF HIGH FLOW CONDITIONS THAT MAY CAUSE SILTATION OR EROSION ARE ENCOUNTERED DURING CONSTRUCTION, WORK SHALL STOP UNTIL THE FLOW SUBSIDES.
- 13. DECKED LOGS SHALL BE ACCESSIBLE FOR INSPECTION.
- 14. LOG TYPE IDENTIFICATION SHALL BE PAINTED ON ALL LOGS IN A PLACE VISIBLE FOR INSPECTION PRIOR TO PLACEMENT WITH LEAD-FREE, BLAZE-ORANGE SURVEY MARKING PAINT
- 15. EXCAVATIONS THAT HAVE POTENTIAL TO IMPACT THE WETTED CHANNEL OF THE SKAGIT RIVER OR SIDE CHANNEL SHALL BE ISOLATED FROM THE ACTIVE CHANNEL. ISOLATION MEANS SHALL CONSIST OF SILT BOOMS, BULK BAGS, BLADDER DAMS OR APPROVED EQUAL AS NECESSARY TO PREVENT IMPACTS TO WATER QUALITY.

SURVEY NOTES:

- BASIS OF BEARINGS IS THE WASHINGTON STATE PLANE COORDINATE SYSTEM, NORTH ZONE, N.A.D. 83/11.
- TOPOGRAPHY SHOWN DEVELOPED FROM LIDAR (2006) AND GROUND SURVEY (SEMARU ENGINEERING AND SURVEYING, 2014).
- VERTICAL DATUM IS NAVD 88. FROM W.S.D.O.T. MONUMENT ID: 7148, ELEVATION = 320.95 FEET, AND MONUMENT ID: 7149, ELEVATION = 323.53 FEET.
- BASE MAP SURVEY CONTROL FILE TO BE PROVIDED TO CONTRACTOR. CONTRACTOR REQUIRED TO MAINTAIN SURVEY CONTROL. STAKING BY DISTRICT IS DESCRIBED IN PROJECT SPECIFICATION.
- 5. EXISTING TRAILS, ROADS, BUILDINGS, WETTED CHANNEL EXTENTS, PARCEL LINES, TREES, AND VEGETATION SHOWN ARE APPROXIMATE.

ABBREVIATIONS

APPROX APPROXIMATE

AVERAGE AVE

BEST MANAGEMENT PRACTICE

CSTC CRUSHED SURFACING TOP COURSE

DIAMETER

ENGINEERED LOG JAM ENGINEERED LOG STRUCTURE ELJ

FLS FT FEET

GROUNDWATER GW

INCHES MAXIMUM MINIMUM NTS NOT TO SCALE


OHW ORDINARY HIGH WATER QTY QUANTITY

TESC

TEMPORARY EROSION AND SEDIMENT CONTROL TYP

WATER SURFACE ELEVATION

LEGEND:



CONCEPT - NOT FOR CONSTRUCTION

HERRERA REVISION BY APP'D DATE




Γ	RUCTION	
	DESIGNED:	DRAWN:
	G. KAYS	E. MARSHALL
i.	DESIGNED:	DRAWN:
E	M. BEGGS	-
ď	DESIGNED:	CHECKED:
	-	-
	SCALE:	APPROVED:
	AGNOTED	M FIMEANIK


PRESSENTIN PARK SIDE CHANNEL RESTORATION

LEGEND AND GENERAL NOTES


FEB 2015 14-05789-000 G-2





th: O:\proj\Y2014/14-05789-000\CAD\Dwgs\C-1.dwg xt Date: 3/30/2015 11:56 AM Cad User: Eric Ma




Path: O:\proj\Y2014\14-05789-000\CAD\Dwgs\C-2.dwg Plot Date: 3/30/2015 11:57 AM Cad User: Eric












BACKFILL WATERWARD OF PILES WITH NATIVE ALLUVIUM EXCAVATION SPOILS

APPROX. LOW WATER SURFACE



GENERAL NOTES:

- 1. PLANT ELJ BACKFILL WITH TREES AND SHRUBS.
- 2. RACKING PLACEMENT SHALL BE COORDINATED WITH LOG LAYER PLACEMENT AND SLASH PLACEMENT TO ENSURE RACKING MEMBERS AND SLASH EXTEND THROUGH RACKING MATERIAL.
- 3. CAP BACKFILL LANDWARD OF PILES WITH 1' OF TOP SOIL TO THE EXTENTS SHOWN ON PLANS.
- 4. EXCAVATION SPOILS SHALL BE STOCKPILED ADJACENT TO EXCAVATION WHILE MAINTAINING ACCESS TO ALLOW LOG LAYER
- 5. RACKING LOGS SHOWN IN THE SECTION SHALL BE INSTALLED WITH APPROXIMATELY 1/3 OF THE LOGS ON THE UPSTREAM FACE OF THE ELJ AND PERPENDICULAR TO THE FLOW, 1/3 PARALLEL TO THE FLOW AND EXTENDING INTO THE CORE OF THE STRUCTURE AND 1/3 PLACED IN RANDOM ORIENTATIONS. PLACEMENT SHALL PRODUCE AN INTERLOCKING/WOVEN EFFECT BETWEEN THE LOG MEMBERS, RACKING, AND SLASH WITH MINIMIZED VOIDS.
- 6. PLACE TETHERED BOULDERS AS SHOWN ON STRUCTURE LAYERING PLAN.

LOG SCHEDULE - LARGE BANK ROUGHENING STRUCTURE:					
LOG TYPE MINIMUM DIAMETER (IN) LENGTH (FT) ROOTWAD		ROOTWAD	TOTAL QTY PER STRUCTURE		
R2	16-24	25	YES	6	
L2	16-24	25	NO	2	
R5	16-24	40	YES	4	
VERT	16-24	25	NO	5	

					HERRERA
					MEKKEKA
No.	REVISION	BY	APP'D	DATE	


	DESIGNED:	DRAWN:	
20000			
-	G. KAYS	E. MARSHALL	
TO WASHING	DESIGNED:	DRAWN:	
1 E W 3	M. BEGGS	-	
	DESIGNED:	CHECKED:	
GISTERED ST	-	-	
O ONALL ENGLY	SCALE:	APPROVED:	
	AS NOTED	M. EWBANK	

PRESSENTIN PARK SIDE CHANNEL RESTORATION


C-6


INLET PLAN AND DETAILS


FEB 2015 14-05789-000




LOG SCHEDULE - FLOOD FENCE STRUCTURE:					
LOG TYPE	MINIMUM DIAMETER (IN) ROOTWAD TOTA STR				
R2	16-24	25	YES	11	
L2	16-24	25	NO	1	
R3	16-24	30	YES	1	
L4	16-24	35	NO	1	
VERT	16-24	25	NO	17	







LEGEND:



GENERAL NOTES:

- 1. PLANT ELJ BACKFILL WITH TREES AND SHRUBS.
- 2. RACKING PLACEMENT SHALL BE COORDINATED WITH LOG LAYER PLACEMENT AND SLASH PLACEMENT TO ENSURE RACKING MEMBERS AND SLASH EXTEND THROUGH RACKING MATERIAL.
- 3. CAP BACKFILL LANDWARD OF PILES WITH 1' OF TOP SOIL TO THE EXTENTS SHOWN ON PLANS.
- EXCAVATION SPOILS SHALL BE STOCKPILED ADJACENT TO EXCAVATION WHILE MAINTAINING ACCESS TO ALLOW LOG LAYER
- RACKING LOGS SHOWN IN THE SECTION SHALL BE INSTALLED WITH APPROXIMATELY 1/3 OF THE LOGS ON THE UPSTREAM FACE OF THE ELJ AND PERPENDICULAR TO THE FLOW, 1/3 PARALLEL TO THE FLOW AND EXTENDING INTO THE CORE OF THE STRUCTURE AND 1/3 PLACED IN RANDOM ORIENTATIONS. PLACEMENT SHALL PRODUCE AN INTERLOCKING/WOVEN EFFECT BETWEEN THE LOG MEMBERS, RACKING, AND SLASH WITH MINIMIZED VOIDS.
- BUILD LARGE BANK ROUGHENING STRUCTURES FIRST, FLOODFENCE STRUCTURE TO BE CONSTRUCTED SO THAT FINAL ELEVATION SHALL BE 318' AT TOP OF LARGE BANK ROUGHENING STRUCTURES.

CONCEPT - NOT FOR CONSTRUCTION


					A
					MEDDED A
					HERRERA
No.	REVISION	BY	APP'D	DATE	


	• • • • • • • • • • • • • • • • • • • •	100.10.1		
Ī		DESIGNED:	DRAWN:	
	-			
	-5	G. KAYS	E. MARSHALL	
	Erot Man	DESIGNED:	DRAWN:	
	1 6 1 1	M. BEGGS	-	
		DESIGNED:	CHECKED:	
	GISTER DE	-	-	
	OF TONAL PAGE	SCALE:	APPROVED:	
	-	AS NOTED	M. EWBANK	

PRESSENTIN PARK SIDE CHANNEL RESTORATION


OUTLET AND FLOODFENCE PLAN AND DETAILS

ATE
DATE:
FEB 2015
PROJECT NO:
14-05789-000
DRAWING NO:
C-7
SHEET NO: OF 9 10





CONCEPT - NOT FOR CONSTRUCTION



SLOPE

1H:1V

3H:1V

4H:1V

E. MARSHAL

PRESSENTIN PARK SIDE CHANNEL RESTORATION

CONTOUR LINE

ANGLE TERMINAL END UPHILL 24" TO 48" TO PREVENT FLOW AROUND WATTLE (TYP)

SPACING

36" O.C.

2" x 2" x 24" UNTREATED WOODEN STAKE

TRENCH, SEE NOTE 1

- 12" MIN OVERLAP (TYP)

STANDARD SPECIFICATION 8-01.3(15).

REMOVAL.

SECTION

WATTLE INSTALLATION ON SLOPE

SPACING VARIES (TYP), SEE WATTLE SPACING TABLE

2" x 2" x 24" WOODEN STAKE (TYP)

NOTES:

2 IN. MIN 5 IN. MAX

WATTLES SHALL BE IN ACCORDANCE WITH THE 2014 WSDOT STANDARD SPECIFICATION 9-14.5(5). INSTALL WATTLES ALONG CONTOURS.

COMPACT EXCAVATED SOIL AND TRENCHES TO PREVENT UNDERCUTTING. ADDITIONAL STAKING MAY BE NECESSARY TO PREVENT UNDERCUTTING.

WATTLES SHALL BE INSPECTED REGULARLY, AND IMMEDIATELY AFTER A RAINFALL PRODUCES RUNOFF, TO ENSURE THEY REMAIN THOROUGHLY ENTRENCHED AND IN CONTACT WITH THE SOIL.

PERFORM MAINTENANCE IN ACCORDANCE WITH THE 2014 WSDOT

REFER TO THE 2014 WSDOT STANDARD SPECIFICATION 8-01.3(16) FOR

INSTALLATION SHALL BE IN ACCORDANCE WITH THE 2014 WSDOT

2. SECURELY KNOT EACH END OF WATTLE. OVERLAP ADJACENT WATTLE ENDS 12" BEHIND ONE ANOTHER AND SECURELY TIE TOGETHER.

4. INSTALL WATTLE PERPENDICULAR TO FLOW ALONG CONTOURS.

4 IN. MAX

8" DIA MINIMUM -

DETAIL

14-05789-000 ESC-1

FEB 2015

WATTLE, SEE DETAIL

8" DIAMETER

WATTLE SPACING TABLE:

MAX SPACING

10 FT

20 FT

30 FT

40 FT

ALLOWABLE **ALTERNATIVE**

TIE-DOWN METHOD

STAGGER OVERLAPS (TYP)

LENGTH VARIES

PLAN

TESC DETAILS

SCALE: NTS

REVISION BY APP'D DATE

HERRERA